

Lap Sealant HS

1. Description

Firestone Lap Sealant HS is designed to seal and mechanically protect the exposed cut edges of QuickSeam Flashing products.

2. Preparation

Surfaces on which Lap Sealant HS is to be applied must be clean, dry, free from loose and foreign materials, oil and grease and primed with QuickPrime Plus. Restore to room temperature prior to use if exposed to temperatures < 15°C for a prolonged period.



3. Application

Apply with a mastic gun a bead of Lap Sealant HS along the properly cleaned, exposed seaming edge. A preformed tool shall be used to feather the bead of sealant. Feathering must take place immediately after the Lap Sealant is applied.

4. Coverage

7 lin.m. per cartridge. Thinning is not allowed.

5. Characteristics

Physical	<ul style="list-style-type: none">• Excellent resistance to ozone, UV and general weathering• Excellent resistance to heat, cold and water
Technical	<ul style="list-style-type: none">• Base rubber polymers• Color black• Solvents light aliphatic solvent• Solids (%) min. 80• Specific gravity 1.34 - 1.46• Flash Point (°C) 11

6. Precautions

Store in original unopened carton at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

Shelf life is expected to be 12 months, when stored in above-mentioned conditions. Shelf life information is only a recommendation and not a fact of life. The actual expiration date depends on the history of storage and handling of the product. Quality and applicability should thus always be verified. Once opened, use within 48 hours.

Refer to Safety Data Sheets. For professional use only. Flammable. Keep away from fire and open flame and other possible ignition sources during storage and use. Do not smoke when using. Use only in well ventilated areas. Avoid prolonged contact with skin. Keep out of reach from children.